


# ANYSHOP® PRIME

Power and Style at Your Space™

- High-End POS System with Alluring Style
- Robust Performance with the 4th Generation Intel® Processors
- Bezel-free True-Flat 15" and 17" LED LCD Display with PCAP Touch
  - Tool-less Design for Rapid Installation and Easy Maintenance
  - Color Customization



## Features & Benefits



### Serve Your Customers Faster

- Intel® Core™ Haswell Processors i3, i5, i7 (Fanless)
- Intel® Celeron™ J1900 Quad-Core Processor (Fanless)



### Make It Easy for Your Staffs

- Bezel-Free 15" and 17" LED LCD Display
- PCAP Touch Activated with Fingers and Gloves



### Make Your Business Look More Attractive

- Sleek and Elegant Design
- Enhance and Differentiate Store Image



### Reduce Your Cost

- Tool-less Design for Rapid Installation
- Service, Maintenance and Upgrade with Ease



### Get Extra Peace of Mind

- Optional Smart Battery for UPS
- Protection from Data Loss and System Damage



### Create Your Own Colors

- Optional Color Customization
- Various Colors for Your Business Needs

# Specifications

General Specifications		Model : Qs(Q3/Q4/Q5), J19
<b>System</b>		
CPU	Q3	Intel® Core™ i3-4100M Processor (3M Cache, 2.40 GHz) / Fanless
	Q4	Intel® Core™ i5-4210M Processor (3M Cache, up to 3.20 GHz) / Fanless
	Q5	Intel® Core™ i7-4600M Processor (4M Cache, up to 3.60 GHz) / Fanless
	J19	Intel® Celeron™ J1900 (2.0 GHz) Quad-Core Processor / Fanless
Chipset	Qs	Intel® HM87 (Co-Lay QM87)
	J19	Intel® Bay Trail
Storage	Qs	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI
	J19	SATA 2 (3Gb/s) 2.5 inch SSD 64GB, Support AHCI
Memory	Qs	2GB Standard (Max. 16GB) Type : DDR3L with 1066 or 1333 MT/s / Socket 1 x SODIMM (Max. 2 Optional)
	J19	2GB Standard (Max. 8GB) Type : DDR3L with 1066 or 1333 MT/s / Socket 2 x SODIMM
	Qs	RAID 0, 1 support
RAID	J19	-
Graphics Controller	Integrated Intel GMA HD	
Audio	2 x 0.8W Stereo Speaker	
<b>LCD Display</b>		
Size / Type	15" TFT LED Backlight	
Resolution	1024 x 768	
Luminance	250 cd/m <sup>2</sup> (typ.)	
<b>Touch Screen</b>		
Type	Projective Capacitive Touch	
Controller Interface	USB Interface	
<b>I/O Interface</b>		
Display Port	1 x VGA	
USB Port	Qs	8 (Rear 6 = USB 3.0 x 4 Ports, USB 2.0 x 2 Ports, Side 2 = USB 2.0 x 2 Ports)
	J19	8 (Rear 6 = USB 3.0 x 1 Port, USB 2.0 x 5 Ports, Side 2 = USB 2.0 x 2 Ports)
PS / 2 Port	1	
Serial Port	3 (COM1 ~ 3 with 5V/12V power output on 9pins)	
Ethernet Port	2 x RJ-45	
Audio	1 x Line-out, 1 x Mic-in	
Power DC-IN	Qs	1 (3pins connector)
	J19	1 (4pins connector)

Power Requirement	
Adapter Input	Qs Adaptor 24V, 5A
	J19 Adaptor 12V, 5A
<b>OS Support</b>	
OS	Windows 7, Windows 8.1, POS Ready 7
<b>Mechanical &amp; Environmental</b>	
Operating Temperature	0°C ~ 50°C at 10% ~ 90% humidity
Storage Temperature	-20°C ~ 80°C at 10% ~ 90% humidity
Dimensions (W x H x D)	365 x 305 x 385 (mm), 14.3 x 15 x 11.2 (inch)
Net Weight	7,500g
Packing Dimension (W x H x D)	380 x 480 x 420 (mm), 15.0 x 18.9 x 16.5 (inch)
Packing Weight	10,000g
Certification	CE, FCC, KC
<b>Optional Configuration</b>	
LCD Display	17" TFT LED Backlight (1280 x 1024 Resolution)
Touch Screen	5-wired Resistive Touch Screen
	2.5 inch SSD 128GB
Storage	2.5 inch HDD 500GB
	2.5 inch HDD 1TB
2nd Storage	2nd 2.5 inch SSD 64GB
	2nd 2.5 inch SSD 128GB
	2nd 2.5 inch HDD 500GB
	2nd 2.5 inch HDD 1TB
I/O Expansion	1 x Cash Drawer Port (RJ11 6pins)
Customer Display (CDP)	VFD (20 columns x 2 lines)
	9.7" 2nd LCD (1024 x 768 Resolution)
2nd Display	12.1" 2nd LCD (1024 x 768 Resolution)
	15" 2nd LCD (1024 x 768 Resolution)
Magnetic Stripe Reader	MSR : Comply with ISO 7811, Support 1 & 2 & 3 track
Smart Card Reader	SCR : EMV level 1, 2
Dallas	Dallas I-button Reader
Battery	Smart Battery : 351P 2050mAh
	Smart Battery : 451P 2050mAh
Color	Custom Colors Available

\*Specifications may change without prior notice.

## Options



Customer Display



2nd Display



Multi-reader (MSR, SCR)



Smart Battery

## Dimension View



## Contact Us



Digicom International Inc  
 155 Rome St  
 Farmingdale, NY 11735  
 Tel: 1-800-689-8999 Fax: 631-249-3688  
 Email: sales@digicomint.com Web: www.digicomint.com